

THE BEST & LAST ROOF COATING YOU'LL EVER USE!



GACOROOF IS IDEAL FOR:

- Aged Asphalt*
- Aged EPDM and TPO/CPA†
- Built-Up
- Cap Sheet
- Composite
- Concrete
- Fiberglass
- Metal
- Modified Bitumen
- Torchdown
- Sprayed Polyurethane Foam
- Most Existing Coatings
- Low-Pitched Roofs
- Flat Roofs
- Mobile Homes
- RVs & Campers

*Not for use on 3-tab asphalt or architectural shingles.

†May require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with a GacoRoof Adhesion Test Kit.

WHITE
GR1600

GRAY
GR1628

GREEN
GR1626

LIGHT TAN
GR1670

RUSTIC
GR1671

MEDIUM BLUE
GR1672

BLACK
GR1673

BROWN
GR1674

RED
GR1675

Note: Colors shown are printed representations of product color. Actual color may vary slightly due to surface texture, application technique and lighting conditions.

FLIP OVER TO COMPARE FOR YOURSELF...

GACOROOF.COM 866 422 6489

GacoFlex
by Gaco Western®

COMPARE FOR YOURSELF



	GacoRoof	Brand X
Warranty	Limited 50-Year	5-10 Years
Can Be Applied Between 32°F and 120°F	YES	NO
Withstands Permanent Ponding Water	YES	NO
Primer/Basecoat Required?	NO*	YES
Recoating Required?	NO	YES

- 2 coat application of same product
Brand X requires multiple products
- Withstands permanent ponding water
Brand X is 48 hours only
- Temperature application range 32°-120°F
Brand X is 50°-90° F
- 1-12 hour cure time, dry to the touch
Brand X is 24-48 hours
- 1 gallon = 100 sq. ft. per coat
Brand X is 1.5 gallons
- Can be used on flat roofs
Brand X requires 1/4" slope
- Can be rained on after 2 hours
Brand X requires no rain, dew or fog within 24-48 hours
- Permanently flexible
Brand X becomes brittle and begins to degrade over time
- Recoat can be done after cure time
Brand X may require 24 hours before recoat
- Silicone Roof Coating
Brand X sells all acrylic roof coatings
- Ponding waterproof
Brand X is ponding water resistant
- 50 year warranty
Brand X 5-10 year warranty
- No polyester mat between coats
Brand X requires polyester mat
- UV resistant
Brand X loses mil thickness due to UV exposure
- 22 mil system
Brand X is 48-60 mil

*Certain applications may require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with a GacoRoof AdhesionTestKit.

GACOROOF.COM 866 422 6489

GacoFlex[®]
by Gaco Western[®]